

1150

MINI LOADER

STRONG ■ COMPACT ■ VERSATILE



THE NOT SO “MINI” LOADER

The 1150 Mini Loader is the largest in the Angry Ant range. Packing a powerful punch, plus the added manoeuvrability of front articulation and hydrostatic 4WD. Powerful enough to handle the heaviest of loads and compact enough to work in tight areas. Quality engineered and backed by an Australian service and parts network, you can rest assured your Ant will give you years of loyal service. With all the attachments available, your Angry Ant is ready to tackle any task you can throw at it.

- Powerful 49 hp Kubota engine
- 5,500kg push/pull capacity
- Easy-to-use joystick operation
- Front articulation
- Hydrostatic 4WD
- Big outreach

3 YEAR
WARRANTY

1300 072 926

globalmachinerysales.com.au
angryantloaders.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
F (03) 9791 7676
E vic@globalmachinerysales.com.au

NSW Unit 1/21 Penny Place Arndell Park 2148
F (02) 8678 2478
E nsw@globalmachinerysales.com.au



1150

MINI LOADER

STRONG ■ COMPACT ■ VERSATILE



▶ Power

Powered by a Kubota 36.5Kw (49 hp) diesel engine with hydrostatic 4WD. Strong telescopic boom combined with front articulation gives the Angry Ant super agility and strength.

▶ Operation

Joystick operation and conveniently located buttons and foot pedals make the Angry Ant easy to operate. Thanks to the quick coupling system changing attachments is simple.

▶ Versatility

The compact size of the Angry Ant and the telescopic boom gives great usability in small spaces. Front and optional rear hydraulic output allows for the attachment of all kinds of machinery. Switch to a different attachment in just one minute with the quick coupling system.

▶ Easy Maintenance

A conveniently located pressure test connector allows for easy diagnosis should a problem arise. The instrument panel has warning lights for all systems and the engine cover is easily removed with 4 bolts.

▶ Safety

ROPS canopy for driver protection, rotating working light, reversing beeper and lights, cylinder protection to prevent boom failure and articulated front to reduce rollover risk.

DY1150 Specifications

Max Length	3410 mm
Max Width	1500 mm
Max Height	2330 mm
Max reach (boom extended)	3540mm
Max reach (boom retracted)	2910mm
Bucket capacity	600L
Rated loading capacity	1600kg (with attachment)
Push/pull capacity (towable load)	5500kg
Min turning radius	2818mm
Turning angle	45 degrees
Speed	16.5 km/h
Weight	2010 kg
Standard tyre	31 x 15.5 -15
Tyre pressure	2.8 bar
Oil tank capacity	70lt
Pressure	200 bar
Working oil flow	82L/min
Tracking oil flow	117L/min
Oil model	L-HL46
Engine	Kubota V2403-E3B
Cylinders	4
Cooling system	Water cooling
Rated Power	36.5 Kw
Rotation speed	2600 r/min
Fuel capacity	32L
Battery	70Ah 12v

3 YEAR
WARRANTY

1300 072 926

globalmachinesales.com.au
angryantloaders.com.au

VIC 24-28 Williams Road Dandenong Sth. 3175
F (03) 9791 7676
E vic@globalmachinesales.com.au

NSW Unit 1/21 Penny Place Arndell Park 2148
F (02) 8678 2478
E nsw@globalmachinesales.com.au

