

### STRONG - COMPACT - VERSATILE



The Angry Ant 620 Mini Loader packs a powerful punch, plus the added manoeuvrability of front articulation and hydrostatic 4WD. Powerful enough to handle the heaviest of loads and compact enough to work in tight areas. Quality engineered and backed by an experienced Australian service and parts network, you can rest assured your Angry Ant will give you many years of loyal service. With all the attachments available, your Angry Ant is ready to tackle any task you can throw at it.

Powerful 30 hp Yanmar engine loads Powerful 30 hp Yanmar engine 2,500kg push/pull capacity Multi-functional joystick Incredibly compact size ROPS/FOPS certified Self-levelling boom

Global

MACHINERY SALES



angryantloaders.com.au

F (03) 9791 7676 E vic@globalmachinerysales.com.au

- NSW Unit 1/21 Penny Place Arndell Park 2148 F (02) 8678 2478
- Ensw@globalmachinerysales.com.au

angry A

# **520** MINI LOADER

## STRONG - COMPACT - VERSATILE



#### Power

Powered by a 30 hp Yanmar engine with hydrostatic 4WD. Strong telescopic boom combined with front articulation gives the Angry Ant super agility and strength.

#### **Operation**

Joystick operation and conveniently located buttons and foot pedals make the Angry Ant easy to operate. Thanks to the quick coupling system changing attachments is simple.

#### Versatility

The compact size of the Angry Ant and the telescopic boom gives great usability in small spaces. Front and optional rear hydraulic output allows for the attachment of all kinds of machinery. Switch to a different attachment in just one minute with the quick coupling system.

#### Easy Maintenance

A conveniently located pressure test connector allows for easy diagnosis should a problem arise. The instrument panel has warning lights for all systems and the engine cover is easily removed with 4 bolts.

#### Safety

ROPS canopy for driver protection, rotating working light, reversing beeper and lights, cylinder protection to prevent boom failure and articulated front to reduce rollover risk.

#### **DY620 Specifications**

Max Length	2195mm
Max Width	980mm
Max Height	2100mm
Max reach (boom extended)	2750mm
Max reach (boom retracted)	2270mm
Bucket capacity	300L
Rated loading capacity	500kg (with attachment)
Push/pull capacity (towable load)	2,500kg
Min turning radius	1980mm
Turning angle	40 degrees
Speed	10 km/h
Weight	1100kg
Standard tyre	23 x 8.5 - 12
Tyre pressure	2.8 bar
Oil tank capacity	35lt
Pressure	190 bar
Working oil flow	16.5L/min x 2
Tracking oil flow	50L/min
Oil model	L-HL46
Engine	30hp Yanmar 3TNV 82A
Cylinders	4
Cooling system	Water cooling
Rated Power	22.2Kw
Rotation speed	2800r/min
Fuel capacity	18L
Battery	55Ah 12v



VIC 24-28 Williams Road Dandenong Sth. 3175 F (03) 9791 7676 E vic@globalmachinerysales.com.au

NSW Unit 1/21 Penny Place Arndell Park 2148 F (02) 8678 2478 E nsw@globalmachinerysales.com.au



Global MACHINERY SALES