NEW B40 MINI LOADER

STRONG - COMPACT - VERSATILE

sil all

The Angry Ant 840 Mini Loader packs a powerful punch, plus the added manoeuvrability of front articulation and hydrostatic 4WD. Powerful enough to handle the heaviest of loads and compact enough to work in tight areas. Quality engineered and backed by an experienced Australian service and parts network, you can rest assured your Angry Ant will give you many years of loyal service. With all the attachments available, your Angry Ant is ready to tackle any task you can throw at it.

Powerful 33 hp Kubota engine
3,500kg push/pull capacity
Multi-functional joystick
Super smooth operation
ROPS/FOPS certified
Hydrostatic 4WD



VIC 24-28 Williams Road Dandenong Sth. 3175 F (03) 9791 7676 E vic@globalmachinerysales.com.au

NSW Unit 1/21 Penny Place Arndell Park 2148 F (02) 8678 2478 E nsw@globalmachinerysales.com.au



Giobal MACHINERY SALES



STRONG - COMPACT - VERSATILE



Power

Powered by a 33 hp Kubota diesel engine with Hydrostatic 4WD. Strong telescopic boom combined with front articulation gives the Angry Ant super agility and strength.

Operation

Joystick operation and conveniently located buttons and foot pedals make the Angry Ant easy to operate. Thanks to the quick coupling system changing attachments is simple.

Versatility

The compact size of the Angry Ant and the telescopic boom gives great usability in small spaces. Front and optional rear hydraulic output allows for the attachment of all kinds of machinery. Switch to a different attachment in just one minute with the quick coupling system.

Easy Maintenance

A conveniently located pressure test connector allows for easy diagnosis should a problem arise. The instrument panel has warning lights for all systems and the engine cover is easily removed with 4 bolts.

Safety

ROPS canopy for driver protection, rotating working light, reversing beeper and lights, cylinder protection to prevent boom failure and articulated front to reduce rollover risk.

DY840 Specifications

Max Length	2600mm
Max Width	1240mm
Max Height	2100mm
Max reach (boom extended)	3000mm
Max reach (boom retracted)	2480mm
Bucket capacity	450L
Rated loading capacity	850kg (with attachment)
Push/pull capacity (towable load)	3,500kg
Min turning radius	2065mm
Turning angle	45 degrees
Speed	12 km/h
Weight	1600kg
Standard tyre	26 x 12 - 12
Tyre pressure	2.8 bar
Oil tank capacity	40lt
Pressure	190 bar
Working oil flow	33.5L/min x 2
Tracking oil flow	78L/min
Oil model	L-HL46
Engine	Kubota V1505-E3B
Cylinders	4
Cooling system	Water cooling
Rated Power	24.5Kw
Rotation speed	2800r/min
Fuel capacity	23L
Battery	60Ah 12v



VIC 24-28 Williams Road Dandenong Sth. 3175 F (03) 9791 7676 E vic@globalmachinerysales.com.au

NSW Unit 1/21 Penny Place Arndell Park 2148 F (02) 8678 2478 E nsw@globalmachinerysales.com.au



Global MACHINERY SALES